



gandharoil

REFINERY (I) LTD

(AN ISO 9001:2000 CERTIFIED)

DIVYOL LOOM OILS

DIVYOL LOOM OILS comprise a range of lubricants which have been specifically designed for all loss systems of textile Looms. These oils have adequate film forming properties and provide better lubrication. These are user friendly in as much as the grades have been formulated to perform well both for boundary as well as full fluid lubrication conditions.

- **Typical Inspections of DIVYOL Loom Oils:-**

Characteristics	Test Methods	DIVYOL LOOM OIL		
		700	320	460
Appearance	Visual	Bright & Clear		
Density at 15°C	D 1298	0.980	0.880	0.885
Flash Point COC°C	D 92	155	155	160
Viscosity cSt at 40°C	D 445	400	320	460
Pour Point °C	D 97	+ 18	+ 8	+ 8

**Corp Off: 1001, 10th Floor, Unique Towers,
Goregaon (W), SV Road, Mumbai 400062, INDIA
TEL: 0091-22-40635600
FAX: 0091-22-40635601
E-MAIL: info@gandharoil.com www.gandharoil.com**



gandharoil

REFINERY (I) LTD

(AN ISO 9001:2000 CERTIFIED)

DIVYOL CONNING OILS

DIVYOL CONNING OILS are specially formulated Anti-Splash Conning Oil suitable for high speed texturing of polyester/nylon filament yarns. Application level of 1.5 to 4% on the weight of the textured yarn is normally recommended which ensures:-

1. Excellent yarn/yarn & yarn/metal lubrication
2. Excellent scourability/antistatic/non-corrosive/non fungal property.
3. Excellent stability of the product during storage of lubricated yarns
4. Low frictional properties which ensures smooth running of the yarn in subsequent processing

S. NO.	CHARACTERISTICS	DIVYA CONNING OIL -20	DIVYA CONNING OIL -30
1.	APPEARANCE	CLEAR	CLEAR
2.	COLOUR (MAX)	<1.5	<2.5
3.	DENSITY @ 30°C gm/ml.	0.850 – 0.886	0.860 – 0.880
4.	FLASH POINT(COC) °C (MIN)	140	160
5.	WATER CONTENT, (MAX)	0.5	0.5
6.	INORGANIC ACIDITY	NIL	NIL
7.	K. VISCOSITY @ 40°C , IN cSt.	14-20	28-32
8.	PH OF THE OIL	7.5	7.5
9.	10% EMULSION STABILITY TEST	PASSES	PASSES

**Corp Off: 1001, 10th Floor, Unique Towers,
Goregaon (W), SV Road, Mumbai 400062, INDIA**

TEL: 0091-22-40635600

FAX: 0091-22-40635601

E-MAIL: info@gandharoil.com

www.gandharoil.com



gandharoil

REFINERY (I) LTD

(AN ISO 9001:2000 CERTIFIED)

--	--	--	--

Corp Off: 1001, 10th Floor, Unique Towers,
Goregaon (W), SV Road, Mumbai 400062, INDIA
TEL: 0091-22-40635600
FAX: 0091-22-40635601
E-MAIL: info@gandharoil.com www.gandharoil.com