

Divyol 4T 20W40 & 20W50 Oils are blended from highly refined base oil with special additive offers extra high performance to impart high oxidation stability, reduce fuel consumption, gear antiwear, extreme pressure properties, sludge and varnish control. Keeps engine clean and long duration intervals.

Meets API SJ, SL, SM JASO MA2 specifications.

Divyol 4T Oils is recommended for new generation 4 stroke motorcycles, scooters and auto rickshaws.

**Performance Benefits:**

- Maximum power output.
- Superior performance in terms of oxidation stability.
- Excellent wear protection at high temperatures and severe operating conditions.
- Outstanding overall engine cleanliness.
- Enhanced engine life
- Higher fuel efficiency.

**Typical Specifications of Divyol 4T Oils:**

Characteristics	Test Method	20W40API SL	20W50 API SL	20W40 API SM
Appearance	Visual	Bright & Clear		
Colour Max.	ASTM D -	Natural		
Viscosity @ 100°C	ASTM D - 445	12.5 to 16.30	16.30 to 21.30	12.5 to 16.30
Viscosity index Min.	ASTM D -	115	110	115
Flash Point COC °C Min.	ASTM D - 92	210	210	210
Pour Point °C Max.	ASTM D - 97	-21	-21	-21
TBN mg KOH/gm oil Min.	ASTM D -	7.0	6.5	7.0

**(Revision # 01 dated 19th June,2018)**

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.