

Divyol Cement Mould Oils is manufactured from highly refined mineral oil base stocks. This has been blended with a special additive to give it a body so that the product offers improved surface finish to the moulded articles.

Applications:

Divyol Cement Mould Oils designed for many types of moulds and formwork where concrete, plaster, tile or paver products are being manufactured.

Typical Specifications of Divyol Cement Mould Oils:

Characteristics	Test Methods	20	Light	Heavy
Appearance	Visual	Bright & Clear		
Viscosity, cst @ 40°C	ASTM D - 445	18 – 22	30 – 45	75 – 80
Flash Point COC °C Min.	ASTM D - 92	165	180	200
Pourpoint °C Max.	ASTM D - 97	+6.0	+6.0	+6.0

(Revision # 01 dated 19th June,2018)

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.



QMS 9001:2015, EMS 14001:2015, OHSAS 18001:2007, NABL Accreditation, GMP Certified and Government Recognised Three Star Export House

Registered Office: 18th Floor, DLH Park, S. V. Road, Goregaon (W), Mumbai 400062, India. CIN: U23200MH1992PLC068905

Phone: +91-22-40635600 • Fax: +91-22-40635601 • E-mail: sales@gandharoil.com, exports@gandharoil.com • **Website: www.gandharoil.com**

Branch Offices & Depot: Pune • Suart • Baroda • Kandla • Indore • Raipur • Udaipur • Jaipur • Delhi • Faridabad • Sonapat • Manesar • Ghaziabad
Hapur • Varanasi • Haridwar • Patna • Haldia • Paradeep • Guwahati • Bangalore • Mangalore • Hyderabad • Vishakhapatnam

Plants: Taloja • Silvassa • Sharjah (U.A.E)

Overseas Office: Dubai • Singapore