

Divyol Gear EP Oils are heavy duty multi-purpose gear oils formulated to give good oxidation stability for long service life. They contain EP additives that withstand high temperature and pour point additive that prevent the lubricant from channeling at low temperatures. These oils can be used in equipment where an API GL4 lubricant is recommended.

Divyol Gear EP Oils meets below specifications:

1. MIL – L – 2105 – EP TYPE
2. IS -1118-1992
3. GL -4

Typical Specifications of Divyol Gear EP Oils:

Characteristics	Test Methods	Divyol Gear					
		EP 80	EP 90	EP 140	EP 75 W 90	EP 80 W 90	EP 85 W 140
Appearance	Visual	Bright & Clear					
Viscosity @ 100°C cst	ASTM D - 445	9 – 12	15 – 21	25 – 34	15 – 21	15 – 21	25 – 34
Viscosity Index Min.	ASTM D - 2270	90	90	85	90	90	85
Flash Point COC °C Min.	ASTM D - 92	180	190	220	180	180	200
Pour Point °C Max.	ASTM D - 97	– 6	– 6	– 6	– 18	– 18	– 18

(Revision # 01 dated 19th June,2018)

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.



QMS 9001:2015, EMS 14001:2015, OHSAS 18001:2007, NABL Accreditation, GMP Certified and Government Recognised Three Star Export House

Registered Office: 18th Floor, DLH Park, S. V. Road, Goregaon (W), Mumbai 400062, India. CIN: U23200MH1992PLC068905

Phone: +91-22-40635600 • Fax: +91-22-40635601 • E-mail: sales@gandharoil.com, exports@gandharoil.com • **Website: www.gandharoil.com**

Branch Offices & Depot: Pune • Suart • Baroda • Kandla • Indore • Raipur • Udaipur • Jaipur • Delhi • Faridabad • Sonapat • Manesar • Ghaziabad • Hapur • Varanasi • Haridwar • Patna • Haldia • Paradeep • Guwahati • Bangalore • Mangalore • Hyderabad • Vishakhapatnam

Plants: Taloja • Silvassa • Sharjah (U.A.E)

Overseas Office: Dubai • Singapore