

Divyol Gear ST Oils are also called as running oils and it can be used for initial fill for short duration. It is fortified with mild EP additives along with anti –oxidant, pour point depressant that prevent channeling at low temperature.

Divyol Gear ST Oils are used for initial fill which helps finishing at mating parts, proper flushing of system to remove swarf & reduces noise. These oils don't corrode yellow metal.

Divyol Gear ST Oils are meet GL3 Performance Level.

Typical Specifications of Divyol Gear ST 90 & 140 Oils:

Characteristics	Test Methods	90	140
Appearance	Visual		
Viscosity @ 100°C cst	ASTM D - 445	15 – 21	25 – 34
Viscosity Index Min.	ASTM D - 2270	95	90
Flash Point COC °C Min.	ASTM D - 92	180	190
Pour Point °C Max.	ASTM D - 97	– 6	– 6

(Revision # 01 dated 19th June,2018)

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.



QMS 9001:2015, EMS 14001:2015, OHSAS 18001:2007, NABL Accreditation, GMP Certified and Government Recognised Three Star Export House

Registered Office: 18th Floor, DLH Park, S. V. Road, Goregaon (W), Mumbai 400062, India. CIN: U23200MH1992PLC068905

Phone: +91-22-40635600 • Fax: +91-22-40635601 • E-mail: sales@gandharoil.com, exports@gandharoil.com • **Website: www.gandharoil.com**

Branch Offices & Depot: Pune • Suart • Baroda • Kandla • Indore • Raipur • Udaipur • Jaipur • Delhi • Faridabad • Sonapat • Manesar • Ghaziabad
Hapur • Varanasi • Haridwar • Patna • Haldia • Paradeep • Guwahati • Bangalore • Mangalore • Hyderabad • Vishakhapatnam

Plants: Taloja • Silvassa • Sharjah (U.A.E)

Overseas Office: Dubai • Singapore