

Divyol Frizol 32 & 68 is manufactured from specially selected base stock to provide low pour point, dryness, good chemical stability and ready solubility in liquefied refrigerant. This product has high fluidity at very low temperature, reduce deposit formation and have reduced tendency to foam.

Divyol Frizol 32 & 68 is recommended for all type of refrigerant except sulfur dioxide. This product has good oxidation and thermal stability and high condenser efficiency.

Divyol Frizol 68 is mainly recommended for Ammonia Compressor.

Typical Specifications of Divyol Frizol Oils:

TEST PARAMETERS	FRIZOL 32	FRIZOL 68
Appearance	Bright & Clear	Bright & Clear
Colour	0.5	0.5
Flash Point COC °C	180 Min	190 Min
Pour Point °C	-35	- 40
Viscosity @ 40 °C	32	68
CU Strip Corrosion	1A	1A
Density @29.5°C	0.86	0.87

(Revision # 01 dated 19th June,2018)

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.



QMS 9001:2015, EMS 14001:2015, OHSAS 18001:2007, NABL Accreditation, GMP Certified and Government Recognised Three Star Export House

Registered Office: 18th Floor, DLH Park, S. V. Road, Goregaon (W), Mumbai 400062, India. CIN: U23200MH1992PLC068905

Phone: +91-22-40635600 • Fax: +91-22-40635601 • E-mail: sales@gandharoil.com, exports@gandharoil.com • **Website:** www.gandharoil.com

Branch Offices & Depot: Pune • Suart • Baroda • Kandla • Indore • Raipur • Udaipur • Jaipur • Delhi • Faridabad • Sonapat • Manesar • Ghaziabad
Hapur • Varanasi • Haridwar • Patna • Haldia • Paradeep • Guwahati • Bangalore • Mangalore • Hyderabad • Vishakhapatnam

Plants: Taloja • Silvassa • Sharjah (U.A.E)

Overseas Office: Dubai • Singapore