

Divyol Snow White Petroleum Jelly are manufactured from blends of waxes & pure oils. Because of its purity it is widely used as base for Ointments, Salves, Veterinary and Cosmetics applications. It is also used extensively in Food Processing, Plastics, Rubber, Tobacco, Paper and Rope Industries.

Packaging Options: DIVYOL Petroleum Jelly are offered in HDPE / Steel Drums & in bulk ISO tanks.

Typical Specifications of Divyol Snow White Petroleum Jelly:

Sr. No.	Test Description	Test Method	DIVYOL SW PJ 54
1	Appearance	Visual	Translucent, soft unctuous, retaining these characters on storage & when melted & allowed to cool without stirring; not more than slightly florescent by day light, even melted; odorless when rubbed on screen.
2	Color	Visual	Snow White
3	Odour	Olfactory	Odourless
4	Density @ 25 °C, gm/ml (TYPICAL)	ASTM D 4052	>0.824
5	Melting Point (°C)	ASTM D 127 °C	54-58
6	Congealing Point (dmm)	ASTM D 938	52
7	Cone Penetration (dmm)	ASTM D 937	145
8	Kinematic Viscosity @ 100 Deg °C (cst)	ASTM D 445	6.25-7.00
9	Sulphated Ash	IP 163	Nil
10	UV Light Absorption	BP 2001	Complies
11	Acidity / Alkalinity	BP 2007	Complies

Customized Petroleum Jelly suiting individual requirement can also be offered.

(Revision # 01 dated 19th June,2018)

Disclaimer: Gandhar makes no warranties, representation or conditions of any kind expressed or implied for use with respect to these products. Final determination of suitability of the product for the application contemplated by the users is solely their responsibility.